

INCLUDED IN BOX

- EPD50 MAX with standard filter holder
- 2 m wire / Euro type F plug
- 2 m wire / UK D-plug
- 125 mm front flange (white)
- 125 mm back flange (white)
- 1 m flex duct 40 mm to fit
- Tie-wrap
- EPHUM-I-DRY humidistat
- 2 m white of controller cord / RJ11 connectors
- QR Code for full user manual



OPTIONAL ADDITIONAL PARTS AVAILABLE

- 125mm input & output flange
- 90mm input and outlet flange
- 10m humidistat extension cord
- Replacement Filter pack of three

PART NUMBER:

EPFLAN125R
EPFLAN90R
EPHUMEXT10M
EPFILPACK FOUR



EPD50 MAX
Information and Manual



EPHUM-I-DRY
Humidity Controller

EPD50 MAX, White Cover with epoxy finish, black paint finish body. Standard filter holder

Technical Data	EPD50 MAX
Extraction @ 35°C / 90% RH	12 litres/day
Typical extraction @ 27°C / 60% RH	10 litres/day
Air Flow (Process Air in)	210 m ³ /hr
Air Flow (Exhaust Air Out)	35 m ³ /hr
Air Flow (Fresh Dry Air Out)	180 m ³ /hr
Mains (Single Phase)	230 V/50 Hz
Current @ 27°C / 60% RH	2.2 A
Power @ 27°C / 60% RH	0.50 kW
Temperature Range	-20 0C - +40 0C
Dimensions LxDxH	328 x 197 x 207 mm
Net Weight	5.7 kg
Noise Level	52 dB

REV1 Subject to Change.



Shipping Code 6008

Made in PRC.

ECOR PRO Ltd
P O BOX 778, Backworth NE27 OBJ, UK
Tel + 44 191 816 2896

POWERED BY

