

INCLUDED IN BOX

- EPD150 RESTO with standard filter holder
- 5 m wire / Euro type F plug (black)
- 5 m wire / UK D-plug (black)
- Inlet Flange (black)
- 1 m flex duct 80 mm to fit
- Black plastic clip



- EPHUM-I-MAX humidistat (WiFi App Enabled)
- 2m "Curley" of controller cord / RJ11 connectors



EPD150 RESTO

DryFan Desiccant Dehumidifier

for Restoration Professionals (Wifi App Enabled)



- EPD150 RESTO, stainless steel cover with epoxy finish black paint finish body.

Technical Data	EPD150 RESTO
Extraction @ 32°C / 90% RH	35 litres/day
Typical extraction @ 20°C / 60% RH	25 litres/day
Air Flow (Process Air in)	380 m ³ /hr
Air Flow (Exhaust Air Out)	75 m ³ /hr
Air Flow (Fresh Dry Air Out)	305 m ³ /hr
Mains (Single Phase)	230 V/50 Hz
Current @ 27°C / 60% RH	3.7 A
Power @ 27°C / 60% RH	0.85 kW
Temperature Range	-20 °C - +40 °C
Dimensions LxDxH	470 x 352 x 345 mm
Net Weight	19 kg
Noise Level	52 dB

REV1 Subject to Change.



Shipping Code 6688

ECOR PRO Ltd
P O BOX 778, Backworth NE27 OBJ, UK
Tel + 44 191 816 2896

POWERED BY



Made in P.R.C.

